



Safety Data Sheet

*** Section 1 - Product and Company Identification ***

Material Name: Slag Cement

Manufacturer Information

CALPORTLAND COMPANY
2025 E. Financial Way
Glendora, CA 91741
Phone: 626-852-6200
www.calportland.com

*** Section 2 - Hazards Identification ***

GHS Classification:

Skin Corrosion/Irritation - Category 2
Eye Damage/Irritation - Category 2B
Carcinogenicity - Category 2
Specific Target Organ Toxicity Single Exposure - Category 3

GHS LABEL ELEMENTS

Symbol(s)



Signal Word

Warning

Hazard Statements

Causes skin irritation.
Causes eye irritation.
Suspected of causing cancer.
May cause respiratory irritation.

Precautionary Statements

Prevention

Wash thoroughly after handling.
Do not eat, drink or smoke when using this product.
Obtain special instructions before use.
Do not handle until all safety precautions have been read and understood.
Wear protective gloves/protective clothing/eye protection/face protection.
Avoid breathing dust.
Use only outdoors or in a well-ventilated area.

Safety Data Sheet

Material Name: Slag Cement

Response

If on skin: Wash with plenty of soap and water. If skin irritation occurs: Get medical advice/attention. Take off contaminated clothing and wash it before reuse.

If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention.

If inhaled: Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor if you feel unwell.

Storage

Store in an appropriate container or containment structure.

Disposal

Dispose of contents/container in accordance with local/regional/national/international regulations.

*** Section 3 - Composition / Information on Ingredients ***

CAS #	Component	Percent
1305-78-8	Calcium oxide	39-43
7631-86-9	Silica, amorphous	31-35
1344-28-1	Aluminum oxide	13-15
1309-48-4	Magnesium oxide	6-8

*** Section 4 - First Aid Measures ***

First Aid: Eyes

Immediately flush eyes thoroughly with water for at least 15 minutes. Call physician if irritation persists.

First Aid: Skin

Wash skin with soap and water. Call physician if irritation persists.

First Aid: Ingestion

Do not induce vomiting. If conscious, have the victim drink plenty of water and call a physician for medical advice.

First Aid: Inhalation

Remove to fresh air. Shortness of breath, coughing, reduced pulmonary function are signs of overexposure. Seek medical help if coughing and other symptoms do not subside.

*** Section 5 - Fire Fighting Measures ***

General Fire Hazards

See Section 9 for Flammability Properties.

None

Hazardous Combustion Products

None

Extinguishing Media

Use appropriate extinguishing media for surrounding fire.

Unsuitable Extinguishing Media

None

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Safety Data Sheet

Material Name: Slag Cement

*** Section 6 - Accidental Release Measures ***

Recovery and Neutralization

Avoid actions that cause dust to become airborne. Avoid inhalation of dust and contact with skin. Wear appropriate personal protective equipment as described in Section 8.

Materials and Methods for Clean-Up

Vacuum cleaning is the preferred method for the dry fine materials. Avoid dry sweeping which creates dust. Apply water spray to prevent airborne dust. Scrape up wet material and place in an appropriate container.

Emergency Measures

Isolate area. Keep unnecessary personnel away.

Personal Precautions and Protective Equipment

Wear appropriate protective equipment and clothing during clean-up.

Environmental Precautions

None

Prevention of Secondary Hazards

None

*** Section 7 - Handling and Storage ***

Handling Procedures

Do not breathe dust which may be created during handling. Use good housekeeping procedures. Do not rely on vision to determine whether respirable silica is present in the air, as it may be present without a visible cloud.

Wash thoroughly after exposure to dust. Promptly remove dusty clothing and launder before reuse.

Storage Procedures

Normal temperatures and pressures do not affect the material.

Incompatibilities

Halogens, acids, combustible materials, metals salts, oxidizing agents.

*** Section 8 - Exposure Controls / Personal Protection ***

Component Exposure Limits

Calcium oxide (1305-78-8)

ACGIH: 2 mg/m3 TWA

OSHA: 5 mg/m3 TWA

NIOSH: 2 mg/m3 TWA

Silica, amorphous (7631-86-9)

NIOSH: 6 mg/m3 TWA

Aluminum oxide (1344-28-1)

OSHA: 15 mg/m3 TWA (total dust); 5 mg/m3 TWA (respirable fraction)

Magnesium oxide (1309-48-4)

ACGIH: 10 mg/m3 TWA (inhalable fraction)

OSHA: 15 mg/m3 TWA (fume, total particulate)

Engineering Measures

Use local exhaust or general dilution ventilation to control exposure within applicable limits.

Safety Data Sheet

Material Name: Slag Cement

Personal Protective Equipment: Respiratory

Avoid actions that cause dust exposure to occur. Use local or general ventilation to control exposures below applicable exposure limits. NIOSH or MSHA approved particulate filter respirators should be used in the context of respiratory protection program meeting the requirements of the OSHA respiratory protection standard [29 CFR 1910.134] to control exposures when ventilation or other controls are inadequate or discomfort or irritation is experienced. Respirator and/or filter cartridge selection should be based on American National Standards Institute (ANSI) Standards Z88.2 Practices for Respiratory Protection.

Personal Protective Equipment: Hands

Where prolonged exposure to products might occur, wear impervious gloves to eliminate skin contact.

Personal Protective Equipment: Eyes

When engaged in activities where ingredients could contact the eye, wear safety glasses with side shields or goggles. In extremely dusty environments and unpredictable environments, wear unvented or indirectly vented goggles to avoid eye irritation or injury. Contact lenses should not be worn when working with ingredients.

Personal Protective Equipment: Skin and Body

Normal work clothing (long sleeved shirts and long pants) is recommended.

* * * Section 9 - Physical & Chemical Properties * * *

Appearance:	Granular mixture	Odor:	No Distinct Odor
Physical State:	Powder	pH:	Not Applicable
Vapor Pressure:	Not Applicable	Vapor Density:	Not Applicable
Boiling Point:	Not Applicable	Melting Point:	Not Applicable
Solubility (H2O):	Insoluble	Specific Gravity:	Not Determined
Evaporation Rate:	Not Applicable	VOC:	Not Applicable
Octanol/H2O Coeff.:	Not Applicable	Flash Point:	None
Flash Point Method:	Not Applicable	Upper Flammability Limit (UFL):	None
Lower Flammability Limit (LFL):	None	Burning Rate:	None
Auto Ignition:	None		

* * * Section 10 - Chemical Stability & Reactivity Information * * *

Chemical Stability

This is a stable material.

Hazardous Reaction Potential

Will not occur.

Conditions to Avoid

Avoid dust generation.

Incompatible Products

Halogens, acids, combustible materials, metals salts, oxidizing agents.

Hazardous Decomposition Products

May form crystalline silica.

Safety Data Sheet

Material Name: Slag Cement

*** Section 11 - Toxicological Information ***

Acute Toxicity

Component Analysis - LD50/LC50

Calcium oxide (1305-78-8)

Oral LD50 Rat 500 mg/kg

Silica, amorphous (7631-86-9)

Oral LD50 Rat >5000 mg/kg; Inhalation LC50 Rat >2.2 mg/L 1 h; Dermal LD50 Rabbit >2000 mg/kg

Aluminum oxide (1344-28-1)

Oral LD50 Rat >5000 mg/kg

Potential Health Effects: Skin Corrosion Property/Stimulativeness

This product can cause abrasion and irritation to the skin.

Potential Health Effects: Eye Critical Damage/ Stimulativeness

Exposure to airborne dust during the handling of this product may cause immediate or delayed irritation and/or abrasion to the cornea.

Potential Health Effects: Ingestion

No known health effect if ingested.

Potential Health Effects: Inhalation

May cause respiratory irritation.

Respiratory Organs Sensitization/Skin Sensitization

This product is not reported to have any sensitization effects.

Generative Cell Mutagenicity

This product is not reported to have any mutagenic effects.

Carcinogenicity

A: General Product Information

Suspected of causing cancer.

B: Component Carcinogenicity

Silica, amorphous (7631-86-9)

IARC: Monograph 68 [1997]; Supplement 7 [1987] (Group 3 (not classifiable))

Magnesium oxide (1309-48-4)

ACGIH: A4 - Not Classifiable as a Human Carcinogen

Reproductive Toxicity

This product is not reported to have any reproductive toxicity effects.

Specified Target Organ General Toxicity: Single Exposure

This product is not reported to have any single exposure specific target organ toxicity effects.

Specified Target Organ General Toxicity: Repeated Exposure

May cause respiratory irritation.

Safety Data Sheet

Material Name: Slag Cement

Aspiration Respiratory Organs Hazard

This product is not reported to have any aspiration hazard effects.

*** Section 12 - Ecological Information ***

Ecotoxicity

A: General Product Information

This product is not reported to have any ecotoxicity effects.

B: Component Analysis - Ecotoxicity - Aquatic Toxicity

Calcium oxide (1305-78-8)

Test & Species

96 Hr LC50 Cyprinus carpio

1070 mg/L [static]

Conditions

Silica, amorphous (7631-86-9)

Test & Species

96 Hr LC50 Brachydanio rerio

5000 mg/L [static]

Conditions

72 Hr EC50 Pseudokirchneriella

440 mg/L

subcapitata

48 Hr EC50 Ceriodaphnia dubia

7600 mg/L

Persistence/Degradability

No information available for the product.

Bioaccumulation

No information available for the product.

Mobility in Soil

No information available for the product.

*** Section 13 - Disposal Considerations ***

Waste Disposal Instructions

See Section 7 for Handling Procedures. See Section 8 for Personal Protective Equipment recommendations.

Disposal of Contaminated Containers or Packaging

Dispose of contents/container in accordance with local/regional/national/international regulations.

*** Section 14 - Transportation Information ***

DOT Information

Shipping Name: Not Regulated

Safety Data Sheet

Material Name: Slag Cement

*** Section 15 - Regulatory Information ***

Regulatory Information

US Federal Regulations

Component Analysis

This material contains one or more of the following chemicals required to be identified under SARA Section 302 (40 CFR 355 Appendix A), SARA Section 313 (40 CFR 372.65) and/or CERCLA (40 CFR 302.4).

Aluminum oxide (1344-28-1)

SARA 313: 1.0 % de minimis concentration (fibrous forms)

State Regulations

Component Analysis - State

The following components appear on one or more of the following state hazardous substances lists:

Component	CAS	CA	MA	MN	NJ	PA	RI
Calcium oxide	1305-78-8	Yes	Yes	Yes	Yes	Yes	No
Silica, amorphous	7631-86-9	Yes	Yes	Yes	Yes	Yes	No
Aluminum oxide	1344-28-1	Yes	Yes	Yes	Yes	Yes	No
Magnesium oxide	1309-48-4	Yes	Yes	Yes	Yes	Yes	No

The following statement(s) are provided under the California Safe Drinking Water and Toxic Enforcement Act of 1986 (Proposition 65):

WARNING! This product contains chemicals known to the state of California to cause cancer, birth defects, or other reproductive harm.

Component Analysis - WHMIS IDL

The following components are identified under the Canadian Hazardous Products Act Ingredient Disclosure List:

Component	CAS #	Minimum Concentration
Calcium oxide	1305-78-8	1 %
Silica, amorphous	7631-86-9	1 %
Aluminum oxide	1344-28-1	1 %
Magnesium oxide	1309-48-4	1 %

Additional Regulatory Information

Component Analysis - Inventory

Component	CAS #	TSCA	CAN	EEC
Calcium oxide	1305-78-8	Yes	DSL	EINECS
Silica, amorphous	7631-86-9	Yes	DSL	EINECS
Aluminum oxide	1344-28-1	Yes	DSL	EINECS
Magnesium oxide	1309-48-4	Yes	DSL	EINECS

Safety Data Sheet

Material Name: Slag Cement

*** Section 16 - Other Information ***

Hazardous Material Information System (HMIS):	Health	1
	Flammability	0
	Physical Hazard	0
	Personal Protection	B

NFPA/HMIS Definitions: 0-Least, 1-Slight, 2-Moderate, 3-High, 4-Extreme

Protective Equipment: Safety glasses, gloves

Key/Legend

EPA = Environmental Protection Agency; TSCA = Toxic Substance Control Act; ACGIH = American Conference of Governmental Industrial Hygienists; IARC = International Agency for Research on Cancer; NIOSH = National Institute for Occupational Safety and Health; NTP = National Toxicology Program; OSHA = Occupational Safety and Health Administration., NJTSR = New Jersey Trade Secret Registry.

Literature References

None

Other Information

SELLER MAKES NO WARRANTY, EXPRESS OR IMPLIED, CONCERNING THE PRODUCT OR THE MERCHANTABILITY OR FITNESS THEREOF FOR ANY PURPOSE OR CONCERNING THE ACCURACY OF ANY INFORMATION PROVIDED BY CALPORTLAND, except that the product shall conform to contracted specifications. The information provided herein was believed by CalPortland Company to be accurate at the time of preparation or prepared from sources believed to be reliable, but it is the responsibility of the user to investigate and understand other pertinent sources of information to comply with all laws and procedures applicable to the safe handling and use of the product and to determine the suitability of the product for its intended use. Buyer's exclusive remedy shall be for damages and no claim of any kind, whether as to product delivered or for nondelivery of product, and whether based on contract, breach of warranty, negligence, or otherwise shall be greater in amount than the purchase price of the quantity of product in respect of which damages are claimed. In no event shall Seller be liable for incidental or consequential damages, whether Buyer's claim is based on contract, breach of warranty, negligence or otherwise.

End of Sheet